







. (1) POWER ON/OFF\*

\*Numbers relate to those shown in the Instructions for Use.

**CONNECTION PORTS\*** 

(6) MATTRESS



You will need:

☐ Tecotherm Neo

☐ TECOmed Coolant Fluid

Prior to operation: Refer to Tecotherm Neo Instructions for Use.


Optional:

☐ Rectal Probe

☐ Skin Probe

☐ Fill-Up Set
□ Connecting Hoses
□ Aqua Pad/ Wrap Mattress
□ Interlayer
Pre-Fill Mattress
☐ A minimum volume of 250 ml TECOmed fluid must be filled into mattress
□ Connect the male mattress connectors to the female connectors of the fill-up bottle
☐ Turn bottle until cap is directed downwards and keep it in a position 0.5m higher than the mattress
Fill-Up the Tecotherm Neo with TECOmed fluid
☐ Ensure mattress hoses are disconnected from the lower pair of device ports (6)
☐ Undo fill-up bottle and fill with TECOmed fluid up to the 450 ml mark
Connect fill-up set to refill port connector counterparts at the device interface (7)
Green marked connector always fits in to the right hand side port.
□ Turn on the Tecotherm Neo, select and start treatment mode "Constant mattress temperature"
☐ Turn bottle until cap is directed downwards
☐ Wait until the fluid level inside fill-up bottle stops falling
□ Now quit treatment mode
☐ Attach the prefilled mattress to hoses and connect to lower device ports (6)
☐ Connect the green marked male connector of the fill-up bottle to the right refill port connector. This time do not connect the left hand male connector
□ Select "Constant mattress temperature" and fill the Tecotherm with another 100 ml of TECOmed fluid
☐ Disconnect fill up set
<b>Note:</b> Move mattress around to ensure all air hubbles have been removed

**Caution:** In servo modes the Tecotherm Neo first pre-conditions the mattress temperature, once rectal probes are inserted press 'START' to commence servo mode otherwise the Tecotherm Neo stays in constant mattress mode.



## **Treatment Modes**

- ☐ In the main menu select the treatment mode required by scrolling to one of, Complete Treatment Mode, Servo Mode or Constant Mattress Temperature Mode
- ☐ Once selected, scroll down and select the parameters to be changed as appropriate
- ☐ Once all parameters are selected press start

**Note:** If using either servo mode you will be asked to insert a rectal probe into the patient and connect to the Tecotherm Neo, if doing so it is recommended to do so by approx 6 cm without forcing the probe so as not to cause internal damage to the patient.



During treatment the screen will display the measured temperature in large numbers. In Servo Modes it will appear in 'Green' if temperature is +/-0.5 °C from set or red if it falls outside of this range. In the Constant Mattress Temperature mode it will appear in Blue (within +/-0.5 °C) or Black if not.

- ☐ If at any time all parameters need to be seen press the 'details' button
- □ From time to time top-up the mattress with TECOmed fluid as described above
   − this can be done without changing the treatment mode or stopping treatment

Note: At any time all parameters can be changed by pressing 'change settings', and selecting the parameter to change.

## Shut Down

Once finished, the Tecotherm Neo can be powered off in the main menu

- ☐ If required, the last treatment can be downloaded to a USB stick by selecting 'Export treatment data' on the main menu
- ☐ Turn the Tecotherm Neo off using the option on the main menu
- ☐ Unplug hoses and mattress and clean with alcohol wipes

The details given in this leaflet are correct at time of going to press. The company reserves the right to improve the products shown.

Distributed by:					



## Inspiration Healthcare Ltd

Gildor House, West Street,

Earl Shilton, Leicester, LE9 7EJ, UK **Tel:** +44 (0) 1455 840 555

**Fax:** +44 (0) 1455 841 464

Email: info@inspiration-healthcare.com
Web: www.inspiration-healthcare.com
24 hour emergency hire and support call

+44 (0) 1455 840 555

500-400(2)